

Terminál OMERO GSM

EMV-Chip	yes
GSM-Data / SMS	yes
SSL GSM GPRS	no
SIM Telefonica O2	only
External Modem	no
ECR-Interface	no
Internal PINPAD	yes

BULL Ingenico 7910 GSM

EMV-Chip	yes
GSM-Data / SMS	yes
SSL GSM GPRS	yes
ISDN-line	yes
SIM Telefonica O2	only
ECR-Interface	no
ECR Version 2.3	only
Internal PINPAD	yes

Most important features:

- GSM terminals with Data/SMS tariff or GPRS
- SIM Telefónica O2
- Without interconnection to ECR
- Requires frequent feeding
- Monitoring of signal intensity

Payment Terminals GSM POS

26. 1. 2009

For electronic acceptance of bank cards Česká spořitelna, a. s. offers terminals Dionica Omero GSM and BULL Ingenico 7910.

These are portable terminals, which are suitable for restaurants, pizzerias and cafés. Mobile terminals are also convenient for locations without standard telephone lines, such as mountain hotels, ski resorts or some petrol stations.

In order to communicate with the authorisation centre this device utilises the GSM signal. Terminal is supplied together with the SIM card and the SMS/data tariff or GPRS in case of SSL terminal. These GSM terminals do not have interface either for communication with a cash-register system or with an external device. Car charger is available for mobile use in a car. Terminal indicates both the intensity of GSM signal and also the status of recharging the battery on its display.

All types of terminals offered by ČS are tested according to the EMV specifications and they are capable of accepting both the magnetic and also chip cards.

All the GSM terminals are equipped with safe internal PINPAD.

List of supported operations:

Sales – Pre-authorisation – Transaction cancellation – Cash – Refund – Pre-authorisation completion – cash back – Quasi cash

Other functions:

Multicurrency and Gratuity.



Supplementary Options

Auxiliary car chargers enhance the spectre of potential use to forwarding companies, delivery services, police forces and taxi. SIM card for the GSM terminal can be provided also by business partners on their costs if the terminal is used in places without O2 signal.